



Standard Test Method for Characterizing the Performance of Refuse Size-Reduction Equipment¹

This standard is issued under the fixed designation E959; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers measuring the performance of solid waste size reduction equipment.

1.2 This test method can be used to measure the flow (that is, throughput) of solid waste through the size-reduction equipment, energy usage of the size-reduction device, and particle size of the shredded product.

1.3 This test method includes instructions for measuring energy usage, solid waste throughput, net processing time, and particle size distribution.

1.4 This test method applies only to size reduction equipment that produces a shredded product with a size corresponding to 90 % cumulative passing in the range of 0.5 to 15 cm (0.2–6 in.) on an air-dry weight basis. For material with nominal sizes outside of this range, the precision and bias statements for particle size designation (Section 14) may not apply.

1.5 This test method can be applied to size reduction equipment located anywhere within a processing line.

1.6 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.6.1 *Exception*—The values given in parentheses are for information only.

1.7 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use. See Section 7 for specific hazard information.*

2. Referenced Documents

2.1 *ASTM Standards*:²

E828 Test Method for Designating the Size of RDF-3 From its Sieve Analysis (Withdrawn 2009)³

E929 Test Method for Measuring Electrical Energy Requirements of Processing Equipment

3. Terminology Definitions:

3.1 *characteristic product size*—the screen size corresponding to 63.2 % cumulative passing by weight.

3.2 *discrete throughput method*—the method whereby average throughput is calculated as the average of a number of discrete throughput measurements conducted during a test period.

3.3 *idling time*—time periods during which a size reduction device is freewheeling, that is, not processing refuse.

3.4 *net processing time*—the time during which refuse is processed through the size reduction device.

3.5 *nominal product size*—the screen size corresponding to 90 % cumulative passing by weight.

3.6 *size reduction device or equipment*—a device which size reduces (Synonyms: shredder, grinder, pulverizer, and mill).

3.7 *stationary belt method*—a method of gross sample collection in which the conveyor belt is stopped and the sample of material is removed manually.

3.8 *time-averaged throughput method*—the method whereby the average throughput is calculated by dividing the total mass size reduced by the net processing time.

3.9 *test interval*—a test interval is equal to one-quarter of the test period.

¹ This test method is under the jurisdiction of ASTM Committee D34 on Waste Management and is the direct responsibility of Subcommittee D34.03 on Treatment, Recovery and Reuse.

Current edition approved Dec. 1, 2010. Published January 2011. Originally approved in 1983. Last previous edition approved in 2005 as E959-83 (2005). DOI: 10.1520/E0959-83R10.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.