



Standard Test Method for Ignitable Liquid Residues in Extracts from Fire Debris Samples by Gas Chromatography-Mass Spectrometry¹

This standard is issued under the fixed designation E 1618; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers the identification of residues of ignitable liquids in extracts from fire debris samples. Extraction procedures are described in the referenced documents.

1.2 While this test method is suitable for all samples, it is especially appropriate for extracts that contain high background levels of substrate materials or pyrolysis products. This guide is also suitable for the identification of single compounds, simple mixtures, or non-petroleum based ignitable liquids.

1.3 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

E 1385 Practice for Separation and Concentration of Flammable or Combustible Liquid Residues from Fire Debris Samples by Steam Distillation²

E 1386 Practice for Separation and Concentration of Flammable or Combustible Liquid Residues from Fire Debris by Solvent Extraction²

E 1387 Test Method for Flammable or Combustible Liquid Residues in Extracts from Fire Debris Samples by Gas Chromatography²

E 1388 Practice for Sampling of Headspace Vapors from Fire Debris Samples²

E 1412 Practice for Separation and Concentration of Flammable or Combustible Liquid Residues from Fire Debris Samples by Passive Headspace Concentration²

E 1413 Practice for Separation and Concentration of Flammable or Combustible Liquid Residues from Fire Debris Samples by Dynamic Headspace Concentration²

E 1459 Guide for Physical Evidence Labeling and Related Documentation²

E 1492 Guide for Receiving, Documenting, Storing, and Retrieving Evidence in a Forensic Laboratory²

3. Summary of Test Method

3.1 The sample is analyzed with a gas chromatograph (GC) which is interfaced to a mass spectrometer (MS) and a data system (DS) capable of storing and manipulating chromatographic and mass spectral data.

3.2 Post-run data analysis generates extracted ion profiles (mass chromatograms) characteristic of the chemical compound types commonly found in ignitable liquids. Additionally, specific chemical components (target compounds) may be identified by their mass spectra and retention times. Semi-quantitative determination of target compounds which are identified by mass spectra and retention time may be used to develop target compound chromatograms (TCCs).

3.2.1 The total ion chromatogram (TIC), extracted ion profiles (EIP) for the alkane, alkene, alcohol, aromatic, cycloalkane, ester, ketone and polynuclear aromatic compound types, or target compound chromatograms (TCC), or combination thereof, are evaluated by visual pattern matching against known reference ignitable liquids.

3.2.2 Ignitable liquids may be grouped into one of eight major petroleum classifications or one miscellaneous class, as described in this test method.

4. Significance and Use

4.1 The identification of an ignitable liquid residue in samples from a fire scene can support the field investigator's opinion regarding the origin, fuel load, and incendiary nature of the fire.

4.1.1 The identification of an ignitable liquid residue in a fire scene does not necessarily lead to the conclusion that a fire was incendiary in nature. Further investigation may reveal a legitimate reason for the presence of ignitable liquid residues.

4.1.2 Due to the volatility of ignitable liquids and to variations in sampling techniques, the absence of detectable quantities of ignitable liquid residues does not necessarily lead to the conclusion that ignitable liquids were not present at the fire scene.

4.2 Materials normally found in a building, upon exposure

¹ This test method is under the jurisdiction of ASTM Committee E30 on Forensic Sciences and is the direct responsibility of Subcommittee E30.01 on Criminalistics. Current edition approved September 10, 2001. Published November 2001. Originally published as E 1618 – 94. Last previous edition E 1618 – 97.

² Annual Book of ASTM Standards, Vol 14.02.