



Designation: F 925 – 9702

Standard Test Method for Resistance to Chemicals of Resilient Flooring¹

This standard is issued under the fixed designation F 925; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This test method provides a procedure for determining the resistance of resilient floor covering to surface deterioration when exposed to various chemical reagents. This test method is not intended as a staining test nor as a method to judge surface and appearance restoration of the sample after exposure to the chemical reagent.

1.2 The values stated in inch-pound units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* Specific precautionary statements are hazard information is provided in Section 6.5 of this test method.

2. Referenced Documents

2.1 *ASTM Standards:*

D 2244 Test Method for Calculation of Color Differences from Instrumentally Measured Color Coordinates²

¹ This practice test method is under the jurisdiction of ASTM Committee ~~F-6~~ F06 on Resilient Floor Coverings and is the direct responsibility of Subcommittee F06.30 on ~~Physical Service Properties—Test Methods—Performance~~.

Current edition approved ~~Sept. 10, 1997; 2002~~. Published ~~June 1998; May 2002~~. Originally published as F 925–85. Last previous edition ~~F 925–96; F 925–97~~.