



Designation: F 1515 – 9803

Standard Test Method for Measuring Light Stability of Resilient Flooring by Color Change¹

This standard is issued under the fixed designation F 1515; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers a procedure for determining the resistance of resilient floor covering to color change from exposure to light over a specified period of time.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:

D 2244 Test Method for Calculation of Color Differences from Instrumentally Measured Color Coordinates²

¹ This test method is under the jurisdiction of ASTM Committee F-6 F06 on Resilient Floor Coverings and is the direct responsibility of Subcommittee F06.30 on Physical Service Properties—Test Methods—Performance.

Current edition approved March 10, 1998; 2003. Published June 1998; May 2003. Originally published as F 1515—95; approved in 1995. Last previous edition approved in 1998 as F 1515 – 978.