NOTICE: This standard has either been superseded and replaced by a new version or discontinued.
Contact ASTM International (www.astm.org) for the latest information.

Designation: F 1667 – 01

Standard Specification for Driven Fasteners: Nails, Spikes, and Staples[1]

This standard is issued under the fixed designation F 1667; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense. The Commercial and Government Entity (Cage) Code for ASTM: 81346.

1. Scope

1.1 This specification covers nails, spikes, staples, and other driven fasteners, as listed in Table 1.

NOTE 1—Fastener ductility information is presented in Table 2 and dimensional information in Tables 3-64.

1.2 Fasteners described in this specification are driven by hand tool, power tool, or mechanical device in single or multiple strikes and may be positioned for striking by hand, tool, or machine.

1.3 The values stated in inch-pound units are to be regarded as the standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*

A 153/A 153M Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware[2]

A 510 Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel[3]

A 641/A 641M Specification for Zinc-Coated (Galvanized) Carbon Steel Wire[2]

B 695 Specification for Coatings of Zinc Mechanically Deposited on Iron and Steel[4]

F 547 Terminology of Nails for Use with Wood and Wood-Base Materials[5]

F 592 Terminology of Collated and Cohered Fasteners and Their Application Tools[5]

F 680 Test Methods for Nails[5]

F 1575 Test Method for Determining Bending Yield Moment of Nails[5]

3. Terminology

3.1 *Definitions*—The definitions used in this specification are those of common commercial acceptance and usage and also appear in Terminologies F 547 and F 592.

4. Classification

4.1 The fasteners and their Table 1 classification are identified as follows:

NOTE 2—The identification of fasteners, classified by style and type (alpha indicators) followed by a dash number (numerical code) based on Tables 3-64, identifies dimensions specifically and establishes a PIN (part identifying number) system when preceded by the F 1667 ASTM designator of this specification. For example:



Identifies a cooler nail with a length of 2⅞, a shank diameter of 0.120, and a head diameter of 0.297 (See Table 10).[A]

[A] All dimensions are given in inches.

4.2 The trade designation, *S*, pennyweight, used in commercial practice is referenced in Tables 3-64 wherever it applies.

5. Ordering Information

5.1 Orders for driven fasteners under this specification shall include the following information:

5.1.1 Quantity or weight;

5.1.2 Part identifying number (PIN) or product description (see 4.1 and appropriate table);

5.1.3 Special material requirements, if specified, including coatings or finishes;

5.1.4 ASTM designation;

5.1.5 Packaging requirements;

[1] This specification is under the jurisdiction of ASTM Committee F16 on Fastenersand is the direct responsibility of Subcommittee F16.05 on Driven and Other Fasteners.

Current edition approved June 10, 2001. Published October 2001. Originally published as F 1667–95. Last previous edition F 1667–00.

[2] *Annual Book of ASTM Standards*, Vol 01.06.

[3] *Annual Book of ASTM Standards*, Vol 01.03.

[4] *Annual Book of ASTM Standards*, Vol 02.05.

[5] *Annual Book of ASTM Standards*, Vol 01.08.

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.