



Standard Practice for Exposing a Membrane Switch to Variation in Atmospheric Pressure¹

This standard is issued under the fixed designation F 1762; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice covers a procedure for exposing a membrane switch to variations in atmospheric pressure. It can be used to determine the effects of pressure variations on chemical and mechanical properties and functional characteristics of the switch.

2. Referenced Documents

2.1 ASTM Standards:²

F 1570 Test Method for Determining the Tactile Ratio of a Membrane Switch

F 1597 Test Method for Determining the Actuation Force and Contact Force of a Membrane Switch

3. Terminology

3.1 Definitions:

3.1.1 *circuit resistance*—electrical resistance as measured between two test points whose internal contacts, when held closed, complete a circuit.

3.1.2 *contact closure*—the event at which a specified resistance is achieved on a membrane switch.

3.1.3 *membrane switch*—a momentary switching device in which at least one contact is on, or made of, a flexible substrate.

3.1.4 *specified resistance*—the maximum allowable circuit resistance as measured between two test points whose internal contacts, when held closed, complete a circuit.

3.1.5 *test points*—two preselected conductive points in a circuit loop, possibly including a switch.

4. Significance and Use

4.1 Erratic operation or malfunction of a membrane switch resulting from changes in the specified switch characteristics,

4.2 Rupture, implosion or explosion of seals due to pressure variations,

4.3 Change in physical or chemical properties due to pressure differentiations, and

4.4 Delaminations of a membrane switch may occur due to pressure variations.

5. Interferences

5.1 Time duration before, during and after pressure cycling,

5.2 Temperature,

5.3 Humidity,

5.4 Mounting Method (if applicable).

6. Apparatus

6.1 *Pressure Chamber*, a chamber or cabinet capable of maintaining a specified pressure. If procedurally required, the apparatus shall be capable of providing pressure variation at a specified rate.

6.2 *Monitoring Device*, suitable to detect contact closure (that is, ohm meter, etc.).

7. Conditioning

7.1 Condition all specimens for 72 h at ambient laboratory conditions immediately prior to exposure, or prior to pressure cycling. This is to enable the specimens to stabilize.

8. Procedure

8.1 Pretest Setup:

8.1.1 Measure or observe the desired characteristics of the switch so that comparable measurements and observations can be made during or after the test.

8.1.1.1 Document the setup, test equipment, and mounting procedure (if applicable) used to measure the characteristics.

8.1.2 Connect predetermined switch terminations to contact closure measuring device.

8.2 In-Process Test:

¹ This test method is under the jurisdiction of ASTM Committee F01 on Electronics and is the direct responsibility of Subcommittee F01.18 on Membrane Switches.

Current edition approved Jan. 10, 2002. Published March 2002. Originally published as F 1762–96. Last previous edition F 1762–97.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

