



Standard Guide for Estimating Oil Spill Recovery System Effectiveness¹

This standard is issued under the fixed designation F1780; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This guide covers the key factors to consider in estimating the effectiveness of containment and recovery systems that may be used to assist in the control of oil spills on water.

1.2 The purpose of this guide is to provide the user with information on assessing the effective use of spill-cleanup equipment. It is intended for use by those involved in planning for and responding to oil spills.

1.3 Sections of this guide describe calculation procedures for estimating recovery system effectiveness. It should be understood that any such calculations cannot be expected to predict system performance, but are intended to provide a common basis for comparing system performance.

1.4 One of the main reasons that the calculation procedures cannot be used to predict system performance is that the analysis is sensitive to assumptions made on the properties of the oil slick, and particularly the changes in slick thickness and emulsification. It is emphasized that the purpose of this guide is not to provide a standard method for estimating slick property changes, but rather to provide a standard guide for using that information in comparing system performance.

1.5 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

2. Referenced Documents

2.1 ASTM Standards:²

F625 Practice for Classifying Water Bodies for Spill Control Systems

F631 Guide for Collecting Skimmer Performance Data in Controlled Environments

F808 Guide for Collecting Skimmer Performance Data in

Uncontrolled Environments (Withdrawn 1997)³

F1523 Guide for Selection of Booms in Accordance With Water Body Classifications

3. Terminology

3.1 Definitions:

3.1.1 *advancing skimmer, n*—a skimmer that is designed to be used to sweep out the spill area.

3.1.1.1 *Discussion*—the skimmer may be independent or may be attached to containment boom to increase sweep width. In some cases, the skimmer may not be attached to the boom but is positioned in the pocket of the boom for skimming. As long as the skimmer operates while moving, it is considered to be an advancing skimmer. Some skimmers are used in both an advancing and stationary mode. These are classified according to their application.

3.1.2 *contained spills, n*—a spill that is restricted from spreading by containment boom or natural means.

3.1.3 *oil slick encounter rate, n*—the volume of oil slick per unit time actively encountered by the oil spill recovery system, and therefore available for containment and recovery (m^3/h).

3.1.4 *oil spill recovery system, n*—a combination of devices that operate together to recover spilled oil; the system would include some or all of the following components: (1) containment boom, (2) skimmer, (3) support vessels to deploy and operate the boom and skimmer, (4) discharge/transfer pumps, (5) oil/water separator, (6) temporary storage devices, and (7) shore based storage/disposal.

3.1.5 *recovery system effectiveness, n*—the volume of oil that is removed from the environment by a given recovery system in a given recovery period.

3.1.6 *recovery period, n*—the time available for recovery systems to carry out cleanup operations.

3.1.7 *response time, n*—the time interval between the spill incident and the start of cleanup operations.

3.1.8 *stationary skimmer, n*—a skimmer that is intended to be used in a fixed location and is moved to new accumulations of oil as skimming progresses.

¹ This guide is under the jurisdiction of ASTM Committee F20 on Hazardous Substances and Oil Spill Response and is the direct responsibility of Subcommittee F20.12 on Removal.

Current edition approved June 1, 2010. Published July 2010. Originally approved in 1997. Last previous edition approved in 2002 as F1780 – 97 (2002). DOI: 10.1520/F1780-97R10.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.