



Designation: F2438 – 04 (Reapproved 2017)

Standard Specification for Oil Spill Response Boom Connection: Slide Connector¹

This standard is issued under the fixed designation F2438; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers design criteria requirements, design geometry, material characteristics, and desirable features for oil spill response boom slide connections. These criteria are intended to define minimum mating characteristics and are not intended to be restricted to a specific configuration.

1.2 The specification defines the geometry required to mate with typical Universal slide connectors or Specification F962 connectors with web thickness up to 0.3 in. Some very heavy-duty or PVC connectors may exceed this dimension and not be compatible.

1.3 The values stated in inch-pound units are to be regarded as standard. No other units of measurement are included in this standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and to determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

F818 Terminology Relating to Spill Response Booms and Barriers

F962 Specification for Oil Spill Response Boom Connection: Z-Connector

F1523/F1523M Guide for Selection of Booms in Accord-

dance With Water Body Classifications

3. Material Characteristics

3.1 End connector and locking pin materials shall be corrosion resistant in seawater and such other environments as the intended service may require. If dissimilar metals are used, care shall be used in design to avoid galvanic corrosion.

3.2 Any material is acceptable for construction of the boom connector provided consideration is given to such factors as weight, mechanical strength, chemical resistance, flexibility, and conditions of the environment in which it is to be used.

4. Design Requirements

4.1 The minimum tensile strength of a boom-to-boom connection shall equal or exceed the minimum fabric tensile strength specified in Table 1 of Guide F1523/F1523M.

4.2 The connector design shall ensure distribution or transfer of the tension member loads from one boom section to the next through or around the end connector in such a manner that the integrity of the joint is not broken at the fabric connection or any supplemental tension member connection(s).

4.3 The connector opening shall be to the right when looking at the top of the connector as shown in Fig. 1.

4.4 The connector or adapter shall not take more than 0.04 in. permanent set when a 250-lb load, distributed over 3 in., is applied. The load shall be applied at the location that results in maximum deflection and shall be resisted by supports placed ½ in. from each end as shown in Fig. 2.

4.5 An end connector shall be long enough to be compatible with the particular boom of which it is a part and not be a limiting member as to the functional freeboard or draft of the membrane.

4.6 The design shall include a tethered, ⅜ in. diameter, self-locking pin, conforming to the dimensional criteria shown in Fig. 3, to resist vertical movement of joined connectors in relation to each other.

4.6.1 The pin's overall length shall be minimized and its ends rounded or chamfered so as to minimize wear and tear on adjacent stored booms or injury to boom handlers.

4.6.2 The pin's spring shall be captured or locked to the pin assembly and shall exert a force on the toggle of between 16 and 22 lbs when connectors are assembled.

¹ This specification is under the jurisdiction of ASTM Committee F20 on Hazardous Substances and Oil Spill Response and is the direct responsibility of Subcommittee F20.11 on Control.

Current edition approved May 1, 2017. Published May 2017. Originally approved in 2004. Last previous edition approved in 2010 as F2438 – 04(2010). DOI: 10.1520/F2438-04R17.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.